

PRODUCT  
DATA SHEET

**FORCE**

August 2014

<b>Type of flooring</b>	<b>EN 653</b>	<b>Resilient Residential PVC floor covering</b>	
<b>Class of use</b>	<b>ISO 10874</b>		
	<b>Class</b>	<b>23</b>	<b>33</b>

## Description



	<b>ISO 24346</b>	<b>2,50 mm</b>		<b>ISO 24341</b>	30m (15-30)   25m (15-25)   22m (15-22)
				Length + Width	2,5/3m   3,5m   4m
	<b>ISO 24340</b>	<b>0,60 mm</b>		<b>ISO 4918</b>	<b>Excellent</b> Castor chair no change of aspect
	<b>prEN 660-1</b>	<b>T</b>		<b>EN ISO 717/2</b>	<b>10 dB</b> Impact sound absorption
	<b>ISO 23997</b>	<b>2,50 kg/m<sup>2</sup></b>		<b>ISO 24343-1</b>	<b>≤ 0,20 mm</b> Residual indentation

## Optional Characteristics

	<b>ISO 105/B02</b>	<b>7/8</b>		<b>EN 1815</b>	<b>-0,2kV -0,8kV</b>		<b>Fire Classification</b> EN 13501-1 Report N° : <b>Bfl-s1</b> <b>RA08-0414</b>
	Light fastness			Static electrical propensity			
	<b>ISO 23999</b>	<b>&lt; 0,1 %</b>		<b>Recyclable</b>	<b>OK</b>	<b>Fungi and bacteria resistance:</b> Does not contribute to infection spreading	
	Dimensional stability						
	<b>EN 12524</b>	<b>0,03 - 0,04 m<sup>2</sup> kW</b>					
	Thermal resistance						


 Manufactured in Serbia by  
TARKETT

EN 14041 : 2004