

TECHNICAL DATA

CERTIFICATION AND CLASSIFICATION	STANDARD	ModularT LL 8	
Type of flooring	EN ISO 10582/EN 651	Heterogeneous Acoustic Resilient Floorcovering	
CE certification	EN 14041:2004 AC:2006		YES
Classification	ISO (EN) 10582/651	 23	Residential: 23 Commercial: 34

TECHNICAL CHARACTERISTICS	STANDARD	ModularT LL 8	
Total thickness	ISO 24346 (EN 428)		4,5 mm
Wear layer thickness	ISO 24340 (EN 429)		0,8 mm
Bevelled edges			YES
Total weight	ISO 23997 (EN 430)		5,2 kg/m ²
Abrasion (wear layer binder content)	ISO 10582		Type I
Form of delivery	ISO 24342		Plank 20 x 120 cm, 9 planks/box = 2,16 m ² Tile 66,5 x 66,5 cm, 6 tiles/box = 2,65 m ²

TECHNICAL PERFORMANCES	STANDARD	ModularT LL 8	
Dimensional stability	ISO 23999 (EN 434)		≤ 0.10 %
Reaction to fire	EN 13501-1		Bfls1
Residual indentation	ISO 24343-1(EN 433)		≤ 0,10 mm
Furniture leg	EN 424		No damage
Castor chair	ISO 4918 (EN 425)		No damage
Curling after exposure to heat	ISO 23999 (EN 434)		≤ 1 mm
Thermal resistance	ISO (EN) 12524		0,02 – 0,03 m ² /KW
Acoustic insulation	ISO (EN) 717/2		13 dB
Index of walking noise	EN ISO 31 – 074		< 67 dB
Light fastness	ISO (EN) 105-B02		≥ 6
Slip resistance	DIN 51130		R9/R10 depending on embossing type
Electrical properties	EN 1815 EN 1081		≤ 2 kV ≤ 1*10 ⁹ Ohm



Floor covering must be installed in accordance with recommendation from producer.