

















CERTIFICATION AND CLASSIFICATION	STANDARD	ModularT 7	
Type of flooring	ISO (EN) 10582	Compact resilient floor covering	
CE certification	EN 14041		YES
Classification	ISO 10874 (EN 685)	  	Residential: 23 Commercial: 34 Industrial: 43

TECHNICAL CHARACTERISTICS	STANDARD	ModularT 7	
Total thickness	ISO 24346 (EN 428)		2,5 mm
Wear layer thickness	ISO 24340 (EN 429)		0,7 mm
Bevelled edges			YES
Total weight	ISO 23997 (EN 430)		3200 g/m ²
Abrasion (wear layer binder content)	ISO 10582		Type I
Form of delivery	ISO 24342 (EN 427)	Plank 20 x 120 cm, 18 planks/box = 4,32m ² , 60 boxes/pallet: 259,2m ² Tiles 60 x 60 cm, 12 tiles/box = 4,32m ² , 60 boxes/pallet: 259,2m ²	

TECHNICAL PERFORMANCES	STANDARD	ModularT 7	
Dimensional stability	ISO 23999 (EN 434)		≤ 0.10 %
Reaction to fire	EN 13501-1		Bfls1 on concrete substrate
Residual indentation	ISO 24343-1(EN 433)		≤ 0,10 mm
Furniture leg	EN 424		No damage
Castor chair	ISO 4918 (EN 425)		No damage
Curl resultant to heat	ISO 23999 (EN 434)		≤ 2 mm
Thermal resistance	ISO (EN) 12524		0,02 - 0,03 m ² K/W
Acoustic insulation	ISO (EN) 717/2		6 dB
Walking noise	NF S 31- 074		L n,e,w = 76 dB
Light fastness	ISO (EN) 105-B02		7/8
Slip resistance	EN 13893 DIN 51130		μ ≥ 0,3 R9/R10 depending on embossing type
Electrical properties	EN 1815 EN 1081		≤ 2 kV ≤ 1*109Ohm



CE 2701-0060-DoP-2019-12
 Manufactured by:
 Tarkett D.O.O. Bačka Palanka
 Industrijska zona 14
 21400 Bačka Palanka
 SERBIA

Floor covering must be installed in accordance with recommendation from producer.