

Product Specifications	Standard	Tiles	Raised Access Floor Tiles (Square and Plank)
Composition	-	75%vinyl + 25% polyester + backing100% vinyl	75%vinyl + 25% polyester + backing100% vinyl
Weight (g/m²) (oz/sq ft)	ISO 8543:1998	2900 g/m² (9.5 oz/sq ft) +13% / -10%	4500 g/m² (14.75 oz/sq ft) +13% / -10%
Thickness (mm.) (in)	ISO 1765:1986	2.25 mm (0.09 in)	2.90 mm (0.11 in)
Light Fastnes (Grey scale: 1-5)	EN ISO 4892:2006 (exterior)	>4/5	>4/5
Light Fastness (Blue scale: 1-8)	EN ISO 105B02:2001 (interior)	>7/8	>7/8
Dimensional Stability %	EN ISO 23999:2012	≤0.25%	≤0.25%
Residual Indentation	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
Castor Chair Test	EN 985:2002	Intensive use	Intensive use
Sound Insulation	EN ISO 10140-3:2011	13 dB	14 dB
Thermal Resistance	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
Static Electricity	EN 1815:1997	< 2 kV	< 2 kV
Slip Resistance	EN 13893:2003	>0.4	>0.4
Slip Resistance	DIN 51130:2014	R10	R10
Slip Resistance	ASTM C1028-96 Static Coefficient	Wet: 0.65; Dry: 0.75	Wet: 0.65; Dry: 0.75
Fire Classification	EN 13501-1:2007	Bfl-S1	Bfl-S1
Fire Classification	ASTM E648 (NFPA 253)	Class 1	Class 1
Antibacterial activity	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
CE Certificate	EN 14041:2004	2895-CPR-SH00981	2895-CPR-SH00981
Use Classification	EN 1307:2014	Heavy Commercial	
Tile Dimensions			