

| Product Specifications                  | Standard                         | Rolls & Tiles  | Raised Access Floor Tiles (Square and Plank)         |
|---|----------------------------------|--|--|
| <b>Composition</b>                      | -                                | 87%vinyl + 13% polyester + backing100% vinyl         | 87%vinyl + % polyester + backing100% vinyl           |
| <b>Weight (g/m²) (oz/sq ft)</b>         | ISO 8543:1998                    | 3500 g/m² (11.5 oz/sq ft) +13% / -10%                | 4275 g/m² (14.0 oz/sq ft) +13% / -10%                |
| <b>Thickness (mm.) (in)</b>             | ISO 1765:1986                    | 2.60 mm (0.10 in)                                    | 3.30 mm (0.13 in)                                    |
| <b>Light Fastness (Grey scale: 1-5)</b> | EN ISO 4892:2006 (exterior)      | >4/5   | >4/5   |
| <b>Light Fastness (Blue scale: 1-8)</b> | EN ISO 105B02:2001 (interior)    | >7/8   | >7/8   |
| <b>Dimensional Stability %</b>          | EN ISO 23999:2012                | ≤0.25%   | ≤0.25%   |
| <b>Residual Indentation</b>             | EN ISO 24343-1:2012              | <0.10 mm (<0.003 in)                                 | <0.10 mm (<0.003 in)                                 |
| <b>Castor Chair Test</b>                | EN 985:2002                      | Intensive use  | Intensive use  |
| <b>Sound Insulation</b>                 | EN ISO 10140-3:2011              | 14 dB  | 15 dB  |
| <b>Thermal Resistance</b>               | EN 12667:2001                    | < 0.15m² K/W   | < 0.15m² K/W   |
| <b>Static Electricity</b>               | EN 1815:1997                     | < 2 kV   | < 2 kV   |
| <b>Slip Resistance</b>                  | EN 13893:2003                    | >0.4   | >0.4   |
| <b>Slip Resistance</b>                  | DIN 51130:2014                   | R9   | R9   |
| <b>Slip Resistance</b>                  | ASTM C1028-96 Static Coefficient | Wet: 0.62; Dry: 0.70                                 | Wet: 0.62; Dry: 0.70                                 |
| <b>Fire Classification</b>              | EN 13501-1:2007                  | Bfl-S1   | Bfl-S1   |
| <b>Fire Classification</b>              | ASTM E648 (NFPA 253)             | Class 1  | Class 1  |
| <b>Antibacterial activity</b>           | ASTM E 2180-18<br>ASTM G21:2013  | Inhibition of bacterial growth & Antifungal activity | Inhibition of bacterial growth & Antifungal activity |
| <b>Roll Width</b>                       | -                                | 200 cm 78.740 in                                     |  |
| <b>Roll Length</b>                      | -                                | 10 lm (32.81 ft)<br>20 lm (65.62 ft)                 |  |
| <b>CE Certificate</b>                   | EN 14041:2004                    | 2895-CPR-SH00981                                     | 2895-CPR-SH00981                                     |
| <b>Use Classification</b>               | EN 1307:2014                     | Heavy Commercial                                     |  |
| <b>Tile Dimensions</b>                  |                                  |  |  |